



व्हीएसटी शक्ती

एमटी 270 - विराट 4डब्ल्यू



भारतातील 8 व्या


फोर व्हील ड्राईव्हच्या
निर्मात्यांकडून



भारतातील सर्वाधिक शक्तीशाली 4 व्हील ड्राईव्ह कॉम्पॅक्ट ट्रॅक्टर



खास वैशिष्ट्ये



फिड पंपसह शक्तीशाली
4 सिलेंडरचे इंजिन



सहज वळविण्यासाठी
पॉवर असिस्टेड
स्टिअरिंग सिस्टम



ऑपरेटरला अधिक सुलभ
काम करता यावे यासाठी
साईड शिफ्ट



स्टिअरिंग व इम्प्लिमेंटच्या
अधिक चांगल्या कार्यासाठी
टॅन्डेम पंप



अॅडजस्टेबल सिटसह
अधिक लेगस्पेस



उच्च कार्यक्षमतेच्या
स्प्रेयरसाठी अनुरूप



750 किलो वजन उचलण्याची
क्षमता असलेले स्मार्ट
हायड्रॉलक्स



डायव्हरला अधिक
आरामशीर वाटावे यासाठी
कार्यशास्त्रानुसार डिझाईन



व्ही.एस्.टी.टिलर्स ट्रॅक्टर लिमिटेड



*विराट 4डब्ल्यूच्या सर्वश्रेष्ठ मॉडेलमध्ये वरील वैशिष्ट्ये उपलब्ध आहेत.

व्हीएसटी शक्ती एमटी 270 विराट 4W तांत्रिक माहिती

इंजिन	
मॉडेल	व्ही4डी
प्रकार	4 सिलेंडर, स्वाभाविक अस्पिरेट केलेले, प्रिकंबशन चेंबर प्रकारचे डिझेल इंजिन
बोअर	73 मि.मी.
स्ट्रोक	78 मि.मी.
डिस्प्लेसमेंट (स्वेट वॉल्यूम)	1306 सीसी
कमाल टॉक	7.0 किलो-एम/2300 आरपीएम
आऊटपुट/रेटेड	27एचपी/3000 आरपीएम
एस्. एफ.सी. (ठराविक इंधन वापर)	210 ग्रॅम/एचपी-तास
कुलिंग यंत्रणा	रेडिएटर कुलिंग
ड्राय वजन	145 किलो
स्टार्ट करण्याची यंत्रणा	12वोल्ट 2 केव्ही स्टार्टर मोटर

इंधन यंत्रणा	
इंधन	हायस्पीड डिझेल
इंधन टाकी क्षमता	18 लिटर
एअर क्लिनर	ऑईल बाथ प्रकारचा सायक्लोनिक प्रिक्लिनरसह

ट्रान्समिशन	
ट्रान्समिशन	स्लाइडिंग मेश प्रकार
फॉरवर्ड	6 स्पीड्स
रिव्हर्स	2 स्पीड्स
प्रवासाचा वेग	1.5 - 22 कि.मी./तास
पॉवर टेकऑफ (पी.टी.ओ.)	2 स्पीड्स, 590 व 870 आरपीएम
स्टॅंडर्ड (पी.टी.ओ.)	540 2750 इंजिन आरपीएम
ब्रेक	अंतर्गत एक्सपांडिंग शू प्रकारचा
टायर्स	पुढचे: 6x12, मागचे: 8.3x20
एकुण आकारमान	2225x1130x1250 (लाxरुxउं)मि.मी.
ग्राउंड क्लिअरन्स	230 मिमी
टर्निंग रेडियस	2.25 एम ब्रेक्ससह आणि 2.7 एम ब्रेक्सशिवाय
हॉलिंग	3 टन
रोटरी	1100 मि.मी./900 मि.मी.
वजन	750 किलो (रोटरीशिवाय)

कामगिरी	
मशागत रुंदी	1100 मि.मी./900 मि.मी.
टाईन्सची संख्या	28/18
मशागतीची खोली	125 मि.मी. कमाल
नांगरणीची खोली	150 मि.मी. कमाल

लाइटिंग यंत्रणा	
लाइटिंग	12 वोल्ट-35 वॅट/35 वॅट
अल्टरनेटर	12 वोल्ट -40 ॲम्पस
ग्लो प्लग	शिथळ प्रकार

वेग / (केएमपीएच)			
गिअर	एल1	1.48	एच1 6.5
	एल2	2.24	एच2 9.84
	एल3	4.94	एच3 21.74
रिव्हर्स	लो		1.89
	हाय		8.3

वैशिष्ट्ये	फायदे	लाभ
 शक्तीशाली व्ही4डी इंजिन	जपानी तंत्रज्ञान	उच्च ताकद व इंधन बचत एकाच वेळी
 टायरचा मोठा आकार	चांगली पकड व रस्त्यावर अधिक वेग	कमी वेळेत अधिक काम
 एडीडीसी यंत्रणा (ऑटोमॅटिक डेपथ व डाफ्ट कंट्रोल)	शेतात डाफ्ट व डेपथवर चांगले नियंत्रण	शेतातील काम करताना इंधनाची अधिक बचत
 मल्टीस्पीड पीटीओ	सर्व पीटीओ कामांसाठी योग्य	विविध प्रकारच्या अवजारांसाठी अधिक चांगली अनुरूपता
 सर्वात कमी टॉक रुंदी	रांगांच्या मधील पिकात सहज काम करते	उस, कापूस, फळबाग लागवडीसाठी उत्तम
 3 स्टेज एअरक्लिअर	इंजिनासाठी स्वच्छ हवा	इंजिनाचे अधिक आयुष्य

उत्पादन द्वारा:

व्ही. एस्. टी. टिलर्स ट्रॅक्टर लिमिटेड

(CIN-L34101KA1967PLC001706)

प्लॉट क्रमांक 39, फेज-1, सिपकॉट औद्योगिक संकुल, मुकुंदपल्ली, होसूर-635 126, तामिळनाडू.

दूरध्वनी: 91-04344-275578 ई-मेल: vstgen.hosur@vsttillers.com

नोंदणीकृत कार्यालय: प्लॉट क्र.1, द्यावसेन्डा औद्योगिक लेआऊट, व्हाईटफिल्ड रोड, महादेवपुरा पोस्ट, बंगलोर-560048

दूरध्वनी: 91-80-67141418 / 23, 67141111 फॅक्स: 91-80-28510221, ई-मेल: sales@vsttillers.com www.vsttillers.com

Follow us on: [f/vsttillers](https://www.facebook.com/vsttillers) [in/company/vst-tillers](https://www.linkedin.com/company/vst-tillers) <http://bit.ly/VSTVideos>

Toll Free Number: **1800 419 0136**

उत्पादनाची आणि त्याच्या जोडण्यांची कामगिरी सामान्य चाचणी परिस्थितीत नमूद करण्यात आली आहे. सातत्यपूर्ण सुधारणांमुळे डिझाईन व तांत्रिक माहितीत बदल होऊ शकतो.

व्हीएसटी शक्ती



व्हीटी-180डी एचएस/जेएआय-4डब्ल्यू

18.5^{HP}



वैशिष्ट्ये

- ✓ विविध उपयोगांसाठी अॅडजस्ट करता येणारे रियर ह्विच
- ✓ ओल्या व सुक्या दोन्ही प्रकारच्या जमिनीत उपयोग करण्यासाठी सर्वाधिक योग्य रोटरी
- ✓ इंजिनाच्या सुधारित कामगिरीसाठी ड्राय प्रकारचा एअर क्लिनर
- ✓ ऑपरेटरला अधिक आराम मिळण्यासाठी नवीन सिट



व्हीएसटी शक्ती व्हीटी-180डी एचएस/जेएआय-4डब्ल्यू ची तांत्रिक माहिती

इंजिन

उत्पादक	व्हीएसटी
इंजिनचे मॉडेल	के3सी
प्रकार	3 सिलेंडर, 4 स्ट्रोक, वॉटर कुलड, इन्डायरेक्ट इंजेक्शन, नॅचरली अस्पिरेटेड, डिझेल इंजिन.
बोअर	70 मि.मी. (2.75 इंच)
स्ट्रोक	78 मि.मी. (3.07 इंच)
डिस्प्लेसमेंट (स्वेट वॉल्यूम)	900.51 क्यू. सीएम (54.9 क्यू.इंच)
कमाल टॉर्क	5.2 किलो-एम (1900 आरपीएम)
आऊटपुट/रेटेड	18.5 एचपी / 2700 आरपीएम (आयएस: 10,000)
एस्. एफ्. सी.	230 जीएम/एचपी-एचआर
कुलिंग सिस्टम	कुलंट आणि पाणी यांचे फोर्स सक्चुरेशन
झाय वेट	125 किलो

इंधन / एअर इन्टेक यंत्रणा

इंधन	हाय स्पीड डिझेल (एच. एस्. डी.)
इंधनाच्या टाकीची क्षमता	18 लिटर
एअर क्लिनर	झाय प्रकारचा

विद्युत यंत्रणा

स्टार्टिंग सिस्टम	स्टार्टर मोटर 12 व्होल्ट्स-1.6 केडब्ल्यू
लाइटिंग	12 व्होल्ट्स, 35 वॅट्स
अल्टरनेटर	12 व्होल्ट्स, 40 ॲम्पस
ग्लो प्लग	12 व्होल्ट्स, क्विक हिट प्रकार

ट्रान्समिशन

ट्रान्समिशन	मेकॅनिकल, कॉन्सन्ट आणि स्लाइडिंग
पुढचे	मेश गियर एकत्रितपणे
मागचे	6 स्पीड
वाहतुकीचा वेग	2 स्पीड्स
पॉवर टेक ऑफ	1.18 केएमपीएच (मि.) / 17.46 केएमपीएच (कमाल)
ब्रेक्स	1-3/8''-एसएई स्टॅंडर्ड स्प्लाईन शाफ्ट, 2 स्पीड्स 540 आणि 1000 आरपीएम.
टायर	वॉटर प्रुफ इंटरनल एक्सपॉझिग शू टाईप ब्रेक पार्किंग ब्रेक्सह
एकुण आकारमान	पुढचा: 5-12, मागचा: 8-18 ट्रॅकची रुंदी 740 व 890.
ग्राउंड क्लिअरन्स	रुंदी 1085 मि.मी., उंची 1230 मि.मी., लांबी 2700 मि.मी., व्हिल बेस 1435 मि.मी.
टर्निंग रेडियस (मि.)	195 मि.मी.
माल वाहून नेण्याची क्षमता	डब्ल्यू/ब्रेक्स 2.1 एम
रोटरी	2 व्हिल ट्रेलर, 3 टन (एकुण वजन)
वजन	साईड ड्राईव्ह प्रकार 645 किलो (डब्ल्यू/ओ बलास्ट वजन)

हायड्रॉलिक यंत्रणा

हायड्रॉलिक यंत्रणा	ऑटो ड्राफ्ट आणि डेपथ कंट्रोल
--------------------	------------------------------

शेतातील कामगिरी

रोटरी	2 पीआर900	2पीआर1100
मशागतीची रुंदी	900 मि.मी.	1100 मि.मी.
टाईन्सची संख्या	20	28
मशागतीची खोली	150 मि.मी.	150 मि.मी.
नांगरणीची खोली	220 मि.मी.	

स्पीड्स

गियर	स्पीड (केएमपीएच)
एल1	1.18
एल2	1.78
एल3	3.94
एच1	5.19
एच2	7.84
एच3	17.46
रिव्हर्स	
एल	1.50
एच	6.65

प्रमुख वैशिष्ट्ये आणि फायदे

झाय प्रकारचे एअर क्लिनर	इंजिनाची अधिक चांगली कामगिरी
अॅडजस्ट करता येणारे हिच	विविध उपयोगांसाठी अॅडजस्ट करता येणारे रिअर हिच
रोटरी सिंक	ओल्या व सुक्याजमिनीतील उपयोगासाठी सर्वाधिक योग्य

उत्पादक:



व्ही.एस्.टी. टिलर्स ट्रॅक्टर लिमिटेड



(CIN - L34101KA1967PLC001706)

प्लॉट क्र.39, फेज-1, सिपकॉट इंडस्ट्रियल कॉम्प्लेक्स, मुकांदपल्ली, होसूर-635126, तामिळनाडू

दूरध्वनी: +91-4344 275578 | vstgen.hosur@vsttillers.com

नॉंदणीकृत कार्यालय: प्लॉट क्र.1, छावासंझा इंड.लेआऊट, व्हाईटफिल्ड रोड, महादेवपुरा पोस्ट, बेंगलुरु-560048, कर्नाटक.

+91-80-67141418/23, 67141111 | vstgen@vsttillers.com



18004190136

[/vsttillers](https://www.facebook.com/vsttillers)

[http://bit.ly/VSTVideos](https://bit.ly/VSTVideos)

[/company/vst-tillers](https://www.linkedin.com/company/vst-tillers)



जबरदस्त कामगिरीची शक्ती मिळवा

विविध हंगामात ।

विविध कामांमध्ये ।

संपूर्ण देशात ।




22 HP

4 Wheel
Drive

व्ही.एस.टी. शक्ती

एमटी 224-1डी एजेआय-4डब्ल्यूबी



ब्रेक्सच्या उत्तम कामगिरीसाठी
ऑईल इमर्सड ब्रेक्स



ड्रायव्हरला अधिक आराम मिळण्यासाठी
अॅडजस्ट करता येणारे सिट





अधिक तास काम करण्यासाठी
ड्राय टाईप एअर क्लिनर

कामाच्या तासांमध्ये वाढ करण्यासाठी
अल्युमिनियम रेडिएटर मेश

हेवी ड्यूटी
फॅडर्स

अधिक माल उचलण्यासाठी
आणि अवजड उपकरणांसाठी
स्मार्ट हायड्रॉलिक्स



टोल फ्री क्रमांक:

1800 419 0136

व्ही.एस.टी. टिलर्स ट्रॅक्टर लिमिटेड



व्हीएसटी शक्ती एमटी 224-1डी/एजेआय 4डब्ल्यूबी ची तांत्रिक माहिती

इंजिन

उत्पादक	व्हीएसटी
मॉडेल	व्ही3डी
प्रकार	3 सिलेंडर
इंजिन एचपी (केब्ल्यू)	22 (16.4) /3000
पीटीओ एचपी (केब्ल्यू)	18.8 (14.0) /3000
रेटेड इंजिन स्पीड	3000 आरपीएम
डिस्प्लेसमेन्ट	980 क्यू. मि.
अॅस्पिरेशन	नॅचरल
कमाल टॉर्क	5.5 किलो-एम (2200 आरपीएम)
एस्.एफ्.सी.	225
कुलिंग सिस्टम यू.एस्.क्यूटी.(एल)	5 लिटर
एअर क्लिनर	ड्राय प्रकारचा
क्रॅककेस	3 लि.

इंधन यंत्रणा

इंधन	हाय स्पीड डिझेल (एच.एस्.डी.)
इंधनाच्या टाकीची क्षमता	18 लि.

ट्रान्समिशन

ट्रान्समिशन	स्ल्यडिंग मेश
प्रकार	मॅन्युअल
पुढे	6 स्पीड्स
मागे	2 स्पीड्स
ट्रॅव्हलिंग स्पीड	19.3 केडब्ल्यू/तास
पॉवर टेक ऑफ	1-3/8''-एसएई स्टॅंडर्ड स्प्लॉइन शाफ्ट, 2 स्पीड्स 692, 1021 आरपीएम 3000 इंज.आरपीएमला
ब्रेक्स	ऑईल इमर्सड ब्रेक्स
टायर	पुढचा: 6×12, मागचा: 8.3×20
एकुण आकारमान	रुंदी 1130 मि.मी., उंची 1250 मि.मी., लांबी 2565 मि.मी., व्हिल बेस 1420मि.मी.
ग्राउंड क्लिअरन्स	230 मि.मी.
ब्रेक्ससह टर्निंग रेडियस (मि.)	2.3
माल वाहून नेण्याची क्षमता	3 टन
ट्रान्समिशन आणि हायड्रॉलिक सिस्टम क्षमता	13 लि.
हायड्रॉलिक सिस्टम कंट्रोल	ऑटो ड्राफ्ट व डेपथ कंट्रोल

कामगिरी

रोटरी टिलिंग रुंदी	900-1100 मि.मी.
स्टिअरिंग	मॅन्युअल
क्लच	ड्राय सिंगल
पंप प्रकार	गियर पंप
कॅटेगरी, 3 पॉइंट हिच	1
हिच लिफ्ट क्षमता, किलो	750

लाइटिंग यंत्रणा

अल्टरनेटर	12 व्होल्ट्स, 40 ॲम्पि.
-----------	-------------------------

उत्पादक:

व्ही.एस्.टी. टिलर्स ट्रॅक्टर्स लिमिटेड

(सीआयएन-एल341401केए1967पीएलसी001706)

प्लॉट क्र.39, फेज-1, सिपकॉट इंडस्ट्रिअल कॉम्प्लेक्स, मुकांदपल्ली, होसूर-635 126, तामिळ नाडू
दूरध्वनी: +91-4344 275578 ई-मेल: vstgen.hosur@vsttillers.com

नोंदणीकृत कार्यालय: प्लॉट क्र.1, द्यावासड्डा इंड.लेआऊट, व्हाईटफिल्ड रोड, महादेवपुरा पोस्ट,
बंगलोर-560048. दूरध्वनी: +91-80-67141418/23, 67141111, फॅक्स: +91-80-28510221.
ई-मेल: sales@vsttillers.com www.vsttillers.com

आम्हाला येथे फॉलो करा: [f/vsttillers](https://www.facebook.com/vsttillers) [in/company/vst-tillers](https://www.linkedin.com/company/vst-tillers) [You Tube http://bit.ly/VSTVideos](https://www.youtube.com/channel/UCVSTtillers)

टोल फ्री क्रमांक: 1800 419 0136

उत्पादनाची आणि ॲटॅचमेन्ट्सची कामगिरी ही प्रमाणित चाचणी परिस्थितीत नमूद करण्यात आली आहे. सातत्यपूर्ण सुधारणेमुळे डिझाईन व तांत्रिक माहितीत बदल होऊ शकतो.



सादर आहे

पूर्णपणे नवीन

**विश्राट
प्लस**

ऑलराउंडर



मजबूत
4 सिलेंडर
इंजिन



बहुगुणी
8 + 2 निरंतर
मेश ट्रान्समिशन



झाय प्रकारातील
एअर क्लीनर



ओआयबी
सिस्टिमसह
प्रभावी ब्रेक



आपल्या वर्गातील
सर्वोत्तम इंधन
क्षमता



1000 किग्रॅपर्यंतच्या
ओइयांसाठी स्मार्ट
हायड्रॉलिक सिस्टिम



सपाट
आरामदायक
प्लॅटफॉर्म



आपल्या वर्गातील
सर्वोत्तम 2.1 मी चे
टर्निंग रेडियस



ताशी
25.5 किमी
चा वेग

टोल फ्री नं : 1800 419 0136

V.S.T. TILLERS TRACTORS LTD.



वैशिष्ट्ये आणि तपशील

	तपशील	प्रकार	लाभ
इंजिन	विनिर्दिष्ट तपशील	ओव्हरहेड व्हॉल्वसह 4 सिलेंडर डिझेल (ओएचव्ही)	अधिक आउटपुटसाठी अधिक मजबूत आणि भौमितिक पद्धतीने संतुलित
	आउटपुट (एचपी)/रेटेड (आरपीएम)	27 @ 2800	पॉवरफुल सुटसुटीत ट्रॅक्टर
	डिसप्लेसमेंट (स्वेट व्हॉल्युम) सीसी		
	बोअर आणि स्ट्रोक (मिमी)	73 & 78	इंजिनाची कमीत कमी कंपनी
	कमाल टॉर्क (किग्रॅ-मी) @ (आरपीएम)	7.2 @ 2200	अचानक आलेला भार सहजपणे हाताळतो
	बॅकअप टॉर्क	8~10%	
	विशिष्ट इंधन वापर (ग्रॅ/एचपी-तास)	190	जास्त बचतीसाठी सर्वोच्च इंधन कार्यक्षमता
	इंधन टाकीची क्षमता (लिटर)	18	
	एअर क्लीनर	झाय टाईप	चांगल्या कार्यक्षमतेसाठी आत येणारी अधिक स्वच्छ हवा
	क्लच	डायफ्राम टाईप 230 मिमी डिआ	उत्कृष्ट गतीशीलतेसाठी मजबूत क्लच
ट्रान्समिशन	कॉनस्टंट मेश	8F + 2R	बदलणारे वेग आणि ओझी यानुसार जास्तीत जास्त इष्टतम चालन
	गीअर लीव्हर	आरएच साईड शिफ्ट	चालकासाठी अधिक चांगल्या आरामाची खात्री मिळते
	व्हील ड्राईव्ह	4 डब्ल्यूडी	शेतीपासून ते वाहणावळीपर्यंत अनेक कामे उत्कृष्टपणे करण्याची क्षमता
	वेग श्रेणी (किमी/ता)	2.6 - 25.5	विशिष्ट चालनासाठी आवश्यकतेनुसार योग्य वेगाची निवड
	स्टॅंडर्ड पीटीओ (आरपीएम)	540 & 1000	पीटीओशी संबंधित चालनासाठी सर्वोत्कृष्टरित्या अनुरूप
	पीटीओ (एचपी)	24	
	भिन्नता	4 स्टार डिफरन्शियल	एका जागी उभा करून अधिक चांगला भार
	ब्रेक्स	ऑईलमध्ये बुडवलेले ब्रेक्स	सुरक्षित आणि विश्वसनीय 'शुअर स्टॉप' तंत्रज्ञान

उत्पादक:

व्ही.एस.टी. टिलर्स ट्रॅक्टर लि.

(CIN- L34101KA1967PLC001706)

प्लॉट क्र. 39, फेज-1, सिपकॉट इंडस्ट्रियल कॉम्प्लेक्स, मुकंदपल्ली, होसुर - 635126, तामिळनाडू.

दूरध्वनी: +91-4344-275578 ईमेल : vstgen.hosur@vsttillers.com

नोंदणीकृत कार्यालय: प्लॉट क्र. 1, द्यावसंग्रा आयएनडीएल. लेआउट, व्हाईटफिल्ड रोड, महादेवपुरा पोस्ट,

बंगलोर - 560 048. दूरध्वनी: +91-80-67141418/23, 67141111, फॅक्स: +91-80-28510221

ईमेल : sales@vsttillers.com, www.vsttillers.com

Follow us on : [/vsttillers](https://www.facebook.com/vsttillers) [/company/vst-tillers](https://www.linkedin.com/company/vst-tillers) [http://bit.ly/VSTVideos](https://www.youtube.com/channel/UCvsttillers)

	तपशील	प्रकार	लाभ
हायड्रॉलिक्स	स्मार्ट हायड्रॉलिक सिस्टिम	ऑटो ड्रॉफ्ट आणि डेप्ट कंट्रोल (ADDC)	1000 किग्रॅ ची ओझी वाहण्यासाठी उच्च-क्षमतेचे स्मार्ट हायड्रॉलिक्स
	उचलण्याची क्षमता (किग्रॅ)	1000	
	वाहणावळ (टन)	4.0	जास्त नफ्यासाठी वाहून नेण्याची आपल्या वर्गातील सर्वोत्तम क्षमता
	तीन बिंदू जोडणी	नवीन श्रेणी 1 डिझाईन	
परिमाणे	एकूण परिमाणे (LxBxH) (मिमी)	2360 x 1130 x 1360	
	ग्राउंड क्लीअरन्स (मिमी)	230	शेतातील कामासाठी सर्वोत्तम
	टर्निंग रेडियस (मी)	2.1	शेताचा प्रत्येक कोपरा सामावून घेण्यासाठी आपल्या वर्गातील सर्वोत्तम
	वजन (किग्रॅ)	900	
	व्हील बेस (मिमी) [L]	1420	सर्व कामांमध्ये अधिक चांगले स्थैर्य आणि कमी घसरतो
	व्हील ट्रॅक (मिमी)	पुढील [a]	870
		मागील [b]	920
	टायर - बाहेरून ते बाहेर (मिमी)	पुढील [c]	1030
		मागील [d]	1130
	जमिनीपासून ते एसआयपी (मिमी)	1087	रांगांतील लागवडीसाठी आदर्श

टोल फ्री नं : 1800 419 0136

उत्पादन आणि त्याच्या संलग्नकांची कामगिरी प्रमाणित चाचणी स्थितीनुसार नमूद केली आहे. सातत्याने होत असलेल्या सुधारणेमुळे रचना आणि विनिर्दिष्ट तपशील बदलू शकतात



बळ हत्तीचे, चॅम्पियन शेतीचे

व्हीएसटी शक्ती

VIRAJ

कामगिरीचा पहेलवान



भारताचा

विन-विन

ट्रॅक्टर

व्हीएसटी शक्ती विराज

इंजिन सिलींडर इंजिन-CC-रेटेड-RPM एअर क्लीनर HP @ रेटेड RPM PTO HP @ रेटेड RPM क्लच	व्हीएसटी शक्ती 9045 DI विराज XT 45 HP 3 सिलींडर 3120 ड्राय टाइप - ड्युअल एलिमेंट 45 HP @ 2000 ERP 42 HP @ 625 PTO RPM ड्युअल	व्हीएसटी शक्ती 9054 DI विराज XP 50 HP 3 सिलींडर 3120 ड्राय टाइप - ड्युअल एलिमेंट 50 HP @ 2200 ERP 45 HP @ 673 PTO RPM ड्युअल
स्टिअरिंग	पॉवर स्टिअरिंग व मेकॅनिकल (वैकल्पिक)	पॉवर स्टिअरिंग
ब्रेक	ऑइल इमर्सड डिस्क ब्रेक	ऑइल इमर्सड डिस्क ब्रेक
ट्रान्समिशन स्पीडसची संख्या स्पीड रेंज (किमी/तास) PTO RPM PTO टाइप	8 फॉरवर्ड व 2 रिव्हर्स 2.10 - 32.38 540 RPM एसटीडी/GSPTO (वैकल्पिक)	8 फॉरवर्ड व 2 रिव्हर्स 2.42 - 33.97 540 RPM एसटीडी/GSPTO (वैकल्पिक)
हायड्रॉलिक हायड्रॉलिक हायड्रॉलिक कंट्रोल सिस्टीम हायड्रॉलिक लिफ्टिंग कॅपॅसिटी थ्री पॉइंट लिंकेज	व्हीएसटी हायड्रॉलक्स ऑटो ड्राफ्ट व डेपथ कंट्रोल (ADDC) 1800 Kg CAT II	व्हीएसटी हायड्रॉलक्स ऑटो ड्राफ्ट व डेपथ कंट्रोल (ADDC) 1800 Kg CAT II
मापने लांबी रुंदी उंची ग्राऊंड क्लियरन्स रीअर टायर साइज फ्रंट टायर साइज	3610 मिमि 1730 मिमि 2160 मिमि 440 मिमि 14.9 X 28 & 12 PR & 13.6 X 28 & 12 PR (वैकल्पिक) 6.00 X 16 / 6.5x16 (वैकल्पिक)	3650 मिमि 1820 मिमि 2270 मिमि 460 मिमि 14.9 X 28 & 12 PR & 16.9 X 28 & 12 PR (वैकल्पिक) 6.5x16 / 7.5x16 (वैकल्पिक)

अतुलनीय वैशिष्ट्ये **



सर्वोत्तम पॉवर प्लोइंग (नांगरणी),
रिवर्सिबल एमपी प्लोच्या सहाय्याने



उच्च परफॉर्मन्स बेलर



सर्वोच्च रोटावेटर कार्य



ओढून नेण्याची अतुलनीय
क्षमता



*अटी व शर्ती लागू

** या जाहिरातील दाखवलेल्या अॅक्सेसरीज फक्त संदर्भासाठी आहेत, आणि त्या स्टॅंडर्ड अॅक्सेसरीजचा भाग नाहीत.

उत्पादक:

व्ही. एस. टी. टिलर्स ट्रॅक्टर लिमिटेड.

नॉदणीकृत कार्यालय : प्लॉट नं. 1, धावसंझा इंड. लेआऊट,
व्हाइफोल्ड रोड, महादेवपुरा पोस्ट, बंगलुरु - 560 048

E-mail : sales@vsttractors.com | www.vsttractors.com

CIN-L34101KA1967PLC001706



Badhte ***KADAM***

**VST SHAKTI
5025 R Branson**

**47
HP**

VST SHAKTI 5025 R

Branson

**POWER
COMFORT
TECHNOLOGY**

POWERED BY VST SHAKTI



**HYDRAULICS WITH
JOY STICK**



**STRONG PTO
HORSE POWER**



**4X4 WHEEL
ENGINE**



LESS VIBRATION



QUIET ENGINE



POWER STEERING



TOP END SPEED

V.S.T. TILLERS TRACTORS LTD. | www.vsttractors.com | Call: 1800 419 0136



Pesh hai

VST SHAKTI
MT 270-HT

**Dumdar torque.
Dumdar diesel ki bachat.**



INDIA KA

WIN-WIN

TRACTOR



VST SHAKTI MT 27

Engine Model

Engine Model	VST 4 Cylinder Engine
Bore (mm)	73
Stroke (mm)	78
Displacement (swept volume) cc	1306
Output (HP) @ Rated (rpm)	27 @2800
Max. Torque (kg-m) @ (rpm)	7.2 @2200
Specific fuel consumption (gms / hp-hr)	205
Cooling system	Water cooled

Transmission

Constant Mesh	8F + 2R
Gear Lever	Side Shift
Speed Range (km / hr)	1.84 - 22.42
STD PTO & ECO PTO (rpm)	540 & 760
PTO (HP)	22
Differential	Bewel Gear
Brake	OIB
Clutch	Single clutch

Fuel System

Fuel	High speed diesel
Fuel Tank Capacity (ltrs) Air Cleaner	18 Dry type

Hydraulic System

Smart Hydraulic System	Auto Draft & Depth Control (ADDC)
Lifting Capacity (kg)	750
Haulage (tonnes)	3
Three Point Linkage	Cat - 1

Overall Dimensions

Overall Dimensions (LxBxH) (mm)	2780 X 1150 X 2075
Ground Clearance (mm)	210
Turning Radius (m)	2.3
Weight (kg)	990
Wheel Base (mm)	1420
Tyre	
Front	6 X 12
Rear	8.3 X 20

Manufactured by :



TILLERS TRACTORS LTD.

CIN-L34101KA1967PLC001706
Plot No.1 Dyavasandra Indl. Layout, Whitefield Road,
Mahadevapura Post, Bengaluru-560048, India.



Ke liye call kare: 1800 419 0136

Authorised dealer:



1-800-4190-136



info@vsttractors.com



www.vsttractors.com



/vst-tillers



http://bit.ly/VSTVideos



company/vst-tillers

नव्या पिढीचा
ट्रॅक्टर

नव्या पिढीच्या
शेतकऱ्यासाठी



VST
NGT 927



फ्युचुरिस्टिक स्टायलिंग



शक्तिशाली चिखलणी
सक्षम केलेला



रचना फळबागांतील
सर्व वापरांसाठी



तेलात बुडवलेले
ब्रेक्स



अचूक हायड्रॉलिक लिफ्टिंग
750 किग्रॅ पर्यंत



ऊसासाठीचे वापर



पॉवर स्टीअरिंग

भारताचा

विन-विन

ट्रॅक्टर

इंजिन मॉडेल	ऊस	फवारणी	चिखलणी
बोर (मिमी)		73	
स्ट्रोक (मिमी)		78	
डिस्प्लेसमेंट (स्वेट वॉल्युम) CC		1306	
आऊटपुट (HP) @ रेटेड (rpm)		24 @ 2700	
कमाल टॉर्क (किग्रॅ - मी) @ (rpm)		7.14	
विशिष्ट इंधन सेवन (gms/hp- दर तास)		205	
		फोर्स वॉटर कूलिंग	
कूलिंग यंत्रणा			
इंधन यंत्रणा		उच्च वेगवान इंधन	
इंधन		18	
इंधनाच्या टाकीची क्षमता (लीटर)		ड्राय टाईप	
एअर क्लीनर			
स्मार्ट हायड्रॉलिक यंत्रणा		ऑटो ड्राफ्ट अँड डेपथ कंट्रोल (ADDC)	
लिफ्टिंग / उचलण्याची क्षमता (किग्रॅ)		750	
मालवाहणी (टन)		3	
थ्री पॉइंट लिंकेज		कॅट - 1	
ट्रान्समिशन			
निवडक स्लायडिंग गिअर		6F + 2R	
गिअर लीव्हर		साइड शिफ्ट	
वेग कक्षा (किमी / तास)	1.51 - 17.09	1.68 - 24.68	1.68 - 19.01
STD PTO आणि ईको PTO (rpm)	646 & 953	549 & 810	646 & 953
PTO (HP)		19.1	
डिफरन्शियल		डिफ. लॉक	
ब्रेक		तेलात बुडवलेला ब्रेक	
एकूण मोजमापे			
एकूण मोजमापे (ला x रुं x उंच) (मिमी)	2450 x 910 x 1376	2450 x 1095 x 1376	2450 x 1095 x 1376
ग्राऊंड क्लिअरन्स (मिमी)		305	
टर्निंग रेडियस OR वळणाची त्रिज्या (मी)		2.3	
एकूण वजन (किग्रॅ)		784	
व्हील बेस (मिमी)		1420	
आऊटर टू आऊटर (मिमी)		890	
		880	
टायर	5x12	6x12	6x12
	8x18	8.3x20	8.3x20



भारताचा **विन-विन**
ट्रॅक्टर



ह्यासाठी कॉल करा : **1800 419 0136**

द्वारे उत्पादित:

वी.एस.टी. टिलर्स ट्रॅक्टर लि.

नोंदणीकृत कार्यालय : प्लॉट क्र. 1, धावसंद इंडस्ट्रियल लेआउट,
व्हाइटफिल्ड रोड, महादेवपुरा पोस्ट, बंगळूर - 560048
ईमेल : sales@vsttractors.com | www.vsttractors.com
CIN-L34101KA1967PLC001706

अधिकृत विक्रेता :

☎ 1800 419 0136

🌐 www.vsttractors.com

✉ sales@vsttractors.com

📘 /vst-tillers

📺 http://bit.ly/VSTVideos

🌐 company/vst-tillers



932 DI & 939 DI

- 2WD & 4WD



VST

Presenting the

OWNER'S TRACTOR



THE PLEASURE OF COMFORT:

- Smooth vibration-free drive
- First ST platform tractor
- Easy gear shifting with fully synchromesh transmission
- Side shift for maximum comfort
- Adjustable suspended seat



EASE OF WORK:

- Independent PTO, reverse PTO & mid PTO
- Finger touch control with double actuating power steering
- Versatile application compatibility for the first time in compact tractors



THE LUXURY OF A CAR:

- Lowest noise tractor
- New-gen instrument cluster
- The comfort of a side shift
- Sleek styling
- Shift gears like your car



1800 419 0136



info@vsttractors.com



www.vsttractors.com



GRAPES



POMEGRANATE



SUGARCANE



SOYABEAN



PADDY



MILLETS



VEGETABLES



MAIZE



COTTON

TECHNICAL SPECIFICATION

AGGREGATES	PARAMETERS	VST 932 DI 2WD/4WD	VST 939 DI 2WD/4WD
ENGINE	Type	Trem IIIA, Naturally Aspirated DI Engine	
	HP (kW) Category	32 (23.5)	39 (28.5)
	No. of Cylinders	3	
	Rated RPM	2500	3000
	Displacement (cc)	1642	
	Cooling	Water Cooled	
	Air Cleaner	Dry Type	
	Max. Torque Nm (Kg-m)	109.4 (11.15)	107.2 (10.93)
TRANSMISSION	PTO HP (kW)	24 (18.65)	28.85 (21.51)
	Gear Box Type	Fully Synchromesh	
	No. of Gears	9 Forward + 3 Reverse	
	Shifting	Side Shift	
	Speed Forward (km/hr)	2.08 - 22.3 / 2.08 - 25.65	2.28 - 28.05
CLUTCH	Speed Reverse (km/hr)	2.21 - 13.86	2.42 - 15.18
	Type	Double Clutch	
PTO	IPTO	540@2340, 1004@2500	
	RPTO	540@1937	
	Mid PTO	Mid PTO	
HYDRAULICS	Type	Auto Draft & Depth Control (ADDC)	
	Three Point Hitch	Category I & II	
	Lifting Capacity (kg)	1250	
BRAKES	Type	Oil Immersed Brakes	
STEERING	Type	Power Steering	
FUEL TANK	Capacity (ltrs)	25	
TYRES	Wheel Drive	2WD / 4WD	
	Front - 2WD	5 x 15	
	Front - 4WD	6 x 12, 7 x 14	
	Rear	9.5 x 20, 11.2 x 24	
DIMENSIONS	Overall Length (mm)	2510	2540
	Overall Width (mm)	Front: 1070, 1190 Rear: 1130 (std), 1470	Front: 1180 Rear: 1245
	Overall Height (mm)	1390	1400
	Wheel Base (mm)	1520	
	Ground Clearance (mm)	325	330
	TCR with Brakes (m)	2.6	
	Total Weight (Kg)	1240 (unballasted)	1260 (unballasted)

Parameters	VST 932	TAFE 30 DI	Swaraj 724 XM	Force OX 25
HP	32	25	24	27
No. of Cylinders	3	2	2	2
Gearbox	H-L-M	L & H	L & H	L & H
No. of Speeds	12	10	8, / 10	10
PTO Power	24	20.3	19.98	23.2



Trust of >5 Lakh Farmers,
Legacy of >50 Years



Widest Product Range
(17 HP to 50 HP)



No.1 Power Tiller Brand
for Last 50 Years



Pioneer in 4WD
Compact Tractors



Global Footprints
in > 40 Countries



Year on Year
Growth Rate > 20%



**VST TILLERS
TRACTORS LTD.**

Regd. Office: Plot No- 1, Dyavasandra Indl. Layout, Whitefield Road,
Mahadevapura Post, Bengaluru-560048, Karnataka. INDIA
Phone: +91 - 80 - 67141111, e-mail: info@vsttractors.com,
CIN: L34101KA1967PLC001706. www.vsttractors.com

Please contact your nearest dealership for latest updates

Authorised Dealer

Disclaimer: Pictures used here are for illustration purpose only. Product specifications are subject to change without prior notice.
Performance of the machine may vary with user/field/working conditions.



1800 419 0136

[f /vsttillers](https://www.facebook.com/vsttillers)

[in /company/vst-tillers](https://www.linkedin.com/company/vst-tillers)

[yt http://bit.ly/VSTVideos](https://www.youtube.com/channel/UCvsttillers)





RUGGED. ROBUST. RADIANT.
THE NEW CLASSIC SERIES



Grow with us

01 3 Feet Tractor (8.3 x 20)



Narrowest width 3 ft – best suitability for sugarcane



Segment first & only 3ft tractor with 8.3 x 20 rear tyres.



Good pulling power and zero slippage

02 Shortest Turning Radius



2.1 m - easy and fastest to turn between rows



Shorter turning radius - easy alignment in next row



No need of bigger headland space

03 Shortest Turning Space with TURBOVATOR



Turbovator integrated with tractor for higher work & zero loss.



**Best in class combination length of 3.1 m
(Tractor + Turbovator)**



More work - less fuel consumption

04 Seamless Integration - Reduces Overhang



Reduces overhang by 260 to 300 mm.



Avoid front end lifting



Enhanced operational efficiency.

05 Best in Class Weight



Zero compaction in root zone
- healthy soil microbiology, healthy crop,
healthy yield.



less soil compaction – better
productivity, soil tilth, and improved
water percolation

06 Optimum Seat Height (970 mm)



Zero damages of fruits even at fully matured stage.



Ease of driving in low height vineyards



Best tractor for grapes spraying.

07 3D Cooling / Overheat Free Operation





**Improved cooling with 64%
opening mesh**



**Front and both side (LH & RH) opening
mesh allows more air flow for enhanced
cooling so over heating problem will not
occur despite longer hours of usage.**

08 Oil Immersed Brakes (OIB)



Better brake efficiency, more operator safety



Longer life of brakes due to less wear and tear

09 Hydraulic Assisted Power Steering (HAPS)



Ease of turning, less effort required, better driving experience.



Less operator fatigue in long hours of usage

10 Adjustable Suspended Seat



More comfort while driving in field for longer hours



Enhanced driving experience with less operator fatigue



Can be adjust to and fro through lever and suitable for all kind of operators.

11 Optimum Ground Clearance (260 mm)



**Higher ground clearance
- ease of bund crossing**



THE MULTI-CROP MECHANIZATION EXPERT



SUGARCANE

- 3 ft tractor - narrowest width
- 3D cooling - over heat free operation
- Shortest turning space with turbovator
- best in combination length



GRAPES

- Highest PTO power for high quality spray
- Best in class seat height
- Low vibration and heat



HORTICULTURE

- Better traction - no wheel slippage
- Ergonomics control - better operator comfort
- 3D cooling - over heat free operation

THE MULTI-CROP MECHANIZATION EXPERT



PADDY

- Optimum weight - zero sinking, ability to pull without sinking
- Fully sealed front axle - no water entry
- Shallow puddling:
More tilling - high yield
Easy transplant - less labour fatigue



ONION & POTATO

- Best in class turning radius
- 3 ft tractor – no damages for furrows and bunds
- High lift capacity - 750 Kg



Product Specification

Model	VST 180D	VST 224-1D	VST 225	VST 270
HP Category	20	24	24	27
Gear box	6+2	6+2	8+2	8+2
Tyre	8-18 / 8.3-20	8-18 / 8.3-20	8-18 / 8.3-20	8-18 / 8.3-20
Tractor Weight	780	800	835	850
Turning Radius	2.4	2.4	2.4	2.4

Application Mapping

Gear box 6+2			Gear box 8+2	
Gears	Speed	Application	Gears	Speed
L1	2.10	Rotary Tiller & Sprayer	L1	2.61
L2	3.18		L2	3.75
L3	5.41		L3	4.9
		Cultivator & Seed Drill	L4	7.05
H1	6.35	Cultivator & Seed Drill	H1	9.52
H2	9.61	Cultivator & Seed Drill (*Only with 6+2)	H2	13.66
H3	16.36	Haulage / Road Work	H3	17.89
			H4	25.8
LR	2.68		LR	2.32
HR	8.11		HR	8.49



Trust of >5 Lakh Farmers,
Legacy of >55 Years



Widest Product Range
(2 HP to 50 HP)



No.1 Power Tiller Brand
for Last 55 Years



Pioneer in 4WD
Compact Tractors



Global Footprints
in > 40 Countries



Year on Year
Growth Rate > 20%



**TILLERS
TRACTORS LTD.**

Regd. Office: Plot No- 1, Dyavasandra Indl. Layout, Whitefield Road, Mahadevapura Post,
Bengaluru - 560 048, Karnataka. INDIA. Phone: 080 6714 1111
CIN: L34101KA1967PLC001706.

86967 97929

www.vsttractors.com

Follow us on:





Grow with us

ABOUT VST GROUP



- VST Group's 100 years legacy is built with the values of 'Trust and Innovation'.
- Established in 1911, initially by supplying petroleum products in the Bangalore Cantonment.
- Group businesses are spread across 7 different sectors like Farm Mechanization, Construction, Petroleum Retails, Automotive Franchise, Exports, Financing & OE Parts Distribution.
- Dedicatedly serving more than 5,000 customers every day.

FOUNDING FATHERS



Mr. V.T. Padmanabhan

Mr. V.T. Krishnamoorthy

Mr. Vellore Singaravelu Thiruvengadaswamy Mudaliar

Mr. V.T. Velu

Confidential & Proprietary information of VST Tillers Tractors Ltd. Reproducing or circulating is strictly prohibited.

Grow with us

5X VISION

We will be a 3000Cr Global brand
in diversified farm mechanization
products and solutions by 2025.

M I S S I O N

WE WILL ACCOMPLISH OUR VISION WITH UNDIVIDED
AND UNDETERRED COMMITMENT TOWARDS INNOVATIVE
QUALITY PRODUCTS, THROUGH INSPIRED INDIVIDUALS,
SIMPLIFIED SYSTEMS AND 5X LEADERSHIP.

VALUES



OUR STORY



Over 50 years ago, the **3 brothers** of the VST Group saw the need for modern, indigenous agri-machinery to support the nation's farmers. Their leadership, dedication and vision established VST Tillers Tractors Ltd. as the first Agriculture based industry in erstwhile **Mysore State**.

VST **started with power tillers**—ideal for cultivating small plots of land, reducing time and strenuous manual labor for Indian farmers. We then applied our expertise to tractors and became **the first manufacturer of compact tractors in India in 1985**.

We have grown thanks to the commitment of our Leaders, Employees, Dealers, Suppliers & Customers and the long-standing trust between us. Growth has always required some form of change. For VST, a company forged in familial bonds of **trust, respect, and cooperation**, it could have been easy to 'outgrow' such simple ideals, especially in times of adversity. However, these **core values** are stronger than ever, and support us as we expand our **reach & mission**.

The **spirit of innovation** that established VST as a pioneer in **Tillers and Compact Tractors** endures as we expand our product range to **higher HP tractors** as well as allied agri-machinery. Our new state-of-the-art factories produce innovative solutions to improve the lives of farmers in India and across **20+ countries globally**. Life in agriculture is often a challenge, but farmers know they can rely on our Tillers and Tractors to make the most of every harvest.

Join us as we look ahead, and *Grow With Us...*

CERTIFICATIONS



Certification	Plant	Year
ISO 9001:1994	Bangalore & Mysore	1998
ISO 9001:2000	Bangalore & Mysore	2001
QS 9000	Mysore	2002
ISO/TS 16949	Mysore	2005
ISO 9001:2008	Bangalore & Mysore	2012
ISO 9001:2008	Hosur	2016
ISO 9001:2015	Hosur, Bangalore, Mysore & Malur	2018

OPPORTUNITIES FOR ALL



Grow with us

Employees

Customers

Partners

Stakeholders

Society

CORPORATE OFFICE

- Location - Bangalore, Karnataka
- Establishment Year - 1970
- Space – 19 Acres



HOSUR PLANT



- Location - Hosur, Tamil Nadu
- Products - Tractors 17 HP to 50 HP
- Establishment Year - 2014
- Space - 15 Acres
- Annual Capacity - 40K Units



MALUR PLANT



- Location - Malur, Karnataka
- Products - Small Farm Mechanization
- Establishment Year : 2018
- Space - 10 Acres
- Annual Capacity - 60 K

MYSURU PLANT



- Location - Mysuru, Karnataka
- Products - Farm Implements & Components
- Establishment Year - 1996
- Space - 5 Acres
- Annual Capacity
 - 60K Tiller Rotary
 - 7K Compact Tractor Rotary
 - 36 K - 5C Tillers
 - 12K - 5C Tractors



CENTRAL WAREHOUSE



- Location - Bangalore, Karnataka
- Products - Spares, Lubricants, Coolants, Grease etc
- Space - 2.29 Acres (inside corporate office)
- SKUs - 6K

PRODUCT CATEGORIES



Tractors



- HT Series - 17 to 27 HP
- NGT & EGT - 20 to 30 HP
- Power Series - 30 & 47 HP
- HHP Series - 40 to 50 HP

Farm Implements & Components



- Rotary Tillers
- Sprayers
- Balers
- Components

Spares, Engines Etc.



- Spares
- Engines
- Lubricants
- Coolants
- Grease

TRACTOR RANGE



HT Series- 2/4 WD

- MT 171 DI – 17 HP
- MT 180 – 18 HP
- 22401D – 22 HP
- MT 270 – 27 HP



NGT Series -4WD

- 927 – 24 HP
- 929 – 27 HP

EGT Series - 4WD

- 9924 – 24 HP
- 9927 – 27 HP



Power Series - 4WD

- 932 – 30 HP



HHP Series – 2 WD

- 9045 HP – 45 HP
- 9054 HP – 50 HP

FARM IMPLEMENT & COMPONENTS



Sprayers

- Air Assisted
- Boom



Rotary Tillers

- Shaktivator (Compact Series)
- Stabilator (HHP Series)



Balers

- Round Mini
- Round Big



Components,

- 5C for Tractor Engines
- 5C for Tiller Engines

SPARES, ENGINES, COOLANTS, LUBRICANTS etc.



Engines

- Horizontal Engines (12 HP to 16 HP)
- Vertical Engines (17 HP to 27 Hp)



Spares

- Liner Piston Sets
- Filters (Fuel, Lubricant, Hydraulic)
- Clutch & Brakes
- Bearings
- Electrical Harnesses & Accessories, Cables
- Engine, Transmission & Body parts
- Rotary Blades & Attachments



Peripherals

- Lubricants
- Coolants
- Grease

GLOBAL PARTNERS



PUBERT France for
Power Weeders & Brush Cutters



ZETOR Tractors Czech Republic for
HHP Tractors



MTD USA for
Brush Cutters



MONARCH Tractors USA for
Electric & Driver Optional Tractors



FARMMECH Taiwan for
Hedge Trimmer & Brush Cutters


INDIA NETWORK



- 3 - Manufacturing Plants
- 15 - Sales Offices
- 40 - Parts Distributors
- 350 - Tractor Dealers
- 500 - SFM Dealers
- 2000 - Retailers



GLOBAL NETWORK (BASED ON FY 20 - 21 SALES)



SHAREHOLDING PATTERN FY 20 - 21



Category	No. of Shareholders	No. of shares held	% to total No. of shares
Promoters/Associates	40	4478665	51.84
Foreign Promoters	1	253125	2.93
Bodies Corporate	205	153228	1.77
Mutual Funds	10	1048874	12.14
Alternate Investment Funds	2	12015	0.14
Banks	3	1763	0.02
Financial Institutions	1	225	0.00
Foreign Financial Institutions	39	567587	6.57
Non-Resident Indians	1023	113721	1.32
Clearing Members	70	11188	0.13
Public/Others	18996	1999137	23.14
Total	20390	8639528	100.00

CSR INITIATIVE



INR 195 Lakhs allocated for CSR funds to promote education and enhance livelihood of the physically disabled.

Media Coverage



Bloomberg the Company & Its Products | The Quint

Search

Bloomberg | Quint

All Sections Markets Business **BQ BLUE** Research Reports Economy & Finance

VST Tillers Tractors - Ambitious Growth Journey Lies Ahead: ICICI Direct

ICICI Direct

Published On 29 Sep 2021, 3:27 PM IST
Last Updated On 29 Sep 2021, 3:27 PM IST

BQ Blue's special research section collates quality and in-depth equity and economy reports from across India's top brokerages, asset managers and research agencies. The reports offer BloombergQuint's subscribers an opportunity to expand their understanding of companies, sectors and the economy.

Save

BusinessLine

HOME NEWS MARKETS COMPANIES INFO
LATEST NEWS | BOOKS | Premium PORTFOLIO | ECONOMY | A

Companies

FARM EQUIPMENT

VST Tillers on products, dealer network expansion drive

G Balachandrar | Chennai | Updated on September 25, 2021



Sees good demand for small farm equipment

VST Tillers Tractors, a leading manufacturer of farm equipment and tractors, is widening its product portfolio in power tiller and other small

moneycontrol

Be a PRO

Coronavirus Markets News Portfolio Commodities Mutual Funds Personal Finance Forum Media Earth360 Invest Now

Business Markets Stocks Economy Companies Trends IPO Opinion

Live Now | Watch New Horizons summit now and learn from eminent experts how technology and innovation can propel our industries forward

Home > News > **OPINION**

We want to be a Rs 3,000-crore company by 2025, says CEO of VST Tillers Tractors

A grip on cost has helped VST Tillers increase profitability despite firmer commodity prices, says Cherukara

MONEYCONTROL OPINION | SEPTEMBER 27, 2021 / 12:03 PM IST

THANK YOU



Nayi Peedhi ki Nayi Pehchaan

Kam Khapath Zyada Taakat



VST 929 DI EGT



Seed drill



Cultivator



Rotavator



Sprayer



3 Cylinder Powerful
Yanmar DI Engine



High
Torque



Dual acting
Power Steering



Superior styling
with great Ergonomics



Front Hood
with Lock



Multi Application
Suitability



Manufactured by :



VST
TILLERS
TRACTORS LTD.

CIN-L34101KA1967PLC001706
Plot No.1 Dyavasandra Indl. Layout, Whitefield Road,
Mahadevapura Post, Bengaluru-560048, India.

Specifications

Aggregates	Parameters	VST 929 DI EGT
Engine	Type	Trem IIIA, Naturally Aspirated Yanmar DI Engine
	HP (kW)	28 HP (20.88 kW)
	No. of Cylinder	3
	Rated RPM	2800
	Displacement (cc)	1331
	Cooling	Water cooled
	Air Cleaner	Dry type - Dual filter
	Torque Kg-m (Nm)	8.6 (84.3 Nm)
	PTO HP (kW)	22 (16.40 kW)
Transmission	Gear Box Type	Constant Mesh
	No.of Gears	8 Forward and 2 Reverse
	Shifting	Side Shift
	Clutch	Single Dry Friction Plate
	Speed forward (kmph)	1.56 - 20.26
	Speed reverse (kmph)	1.39 - 5.05
Brakes	Type	Oil Immersed Brakes
Steering	Type	Power Steering
PTO	Type	Dual PTO
	RPM	540, 540E
Fuel Tank	Capacity (Litre)	24
Hydraulics	Type	ADDC – Automatic Depth and Draft Control
	Three Point Hitch	Category I
	Lifting Capacity (Kg)	750
Tyres	Wheel drive	4 Wheel Drive
	Front	6.00 x 12
	Rear	8.30 x 20
Dimensions	Overall length (mm)	2530
	Overall width (mm)	1040-1095
	Overall Height (mm)	1323
	Wheel base(mm)	1520
	Ground Clearance (mm)	305
	Turning Circle Radius with brakes(m)	2.1
	Total Weight (Kg)	860 Without ballast

Authorised dealer:



CUSTOMER HELPLINE: 1800 4190 136

 info@vsttractors.com

 www.vsttractors.com

 [/vst-tillers](https://www.facebook.com/vst-tillers)

 <http://bit.ly/VSTVideos>

 [company/vst-tillers](https://www.linkedin.com/company/vst-tillers)

09/2022



PREMIUM RANGE OF TRACTORS WITH WORLD-CLASS TECHNOLOGY



TECHNICAL SPECIFICATIONS

Model Name	VST ZETOR 5011	VST ZETOR 4511	VST ZETOR 4211
ENGINE			
Power (@2100 rpm)	49 HP (36.5 kW)	45 HP (33.5 kW)	42 HP (31.3 kW)
No. of Cylinder	3		
Displacement (cc)	2942		
Air Cleaner	Dry Type		
Max. Torque (Nm)	205	190	180
PTO			
PTO Type	540/ GSPTO		
TRANSMISSION			
Transmission Type	Fully Constant Mesh – HCR		
No.of Gears	8+2		
Gear Shift	Side Shift		
Rear Axle Reduction	BullGear Pinion		
SPEED & CLUTCH			
Speed forward (km/h)	2.6-34.1	2.4-32.5	2.3-31.1
Speed reverse (km/h)	3.2-12.7	3.1-12.1	2.9-11.6
Forward Speed at flyup	37.1	35.5	33.9
Clutch	Dual		Dual /Single*
BRAKES			
Type	Oil Immersed Brakes		
STEERING			
Type	DAPS		DAPS/SAPS*
SEAT			
Type	Premium Adjustable VZ Seat		
FUEL TANK			
Capacity (L)	60		

Model Name	VST ZETOR 5011	VST ZETOR 4511	VST ZETOR 4211
HYDAULICS			
Three Point Linkage	CAT II		
Lift o Matic	yes		
Lifting Capacity (kg)	Automatic Depth and Draft Control - 1800 kg		
Spool Valve	DCV		DCV/QRC*
WHEEL			
Wheel drive	2WD		
Front	190.50 mm X 406.40mm (7.5 x 16)/ 165.10 mm X 406.40 mm (6.5 x 16)*	165.10 mm X 406.40mm (6.5 x 16)/ 152.40 mm X 406.40 mm (6.00 x 16)*	152.40 mm X 406.40 mm (6.00 x 16)
Rear	429.26 mm X 711.20 mm (16.9 x 28)/ 378.46 mm X 711.20 mm (14.9 x 28)*	378.46 mm X 711.20 mm (14.9 x 28)/ 345.44 mm X 711.20 mm (13.6 x 28)*	345.44 mm X 711.20 mm (13.6 x 28)
ELECTRICAL			
Battery	12 V , 88 Ah		
Alternator	12 V, 50 A		
Starter Motor	12 V , 2.7 kW		
DIMENSIONS			
Overall length (mm)	3570	3570	3570
Overall width (mm)	1930	1820	1750
Overall Height (mm)	2120	2110	2090
Ground Clearance (mm)	460	440	420
Wheel base (mm)	2100	2100	2100
Total weight (kg)	2210	2140	2080

*Optional

Please contact your nearest dealership for latest updates

Authorised Dealer

VST ZETOR PRIVATE LIMITED

Plot No-1, Dyavasandra Industrial Layout,
Mahadevapura Post, Bangalore-560048, Karnataka, India.
e-mail: info@vstzetur.com; www.vstzetur.com
CIN: U28211KA2023PTC179152



1800 419 0136

Disclaimer: Pictures used here are for illustration purpose only.
Product specifications are subject to change without prior notice.
Performance of the machine may vary with user/field/working conditions.



932 DI & 939 DI

- 2WD & 4WD



VST

Presenting the

OWNER'S TRACTOR



THE PLEASURE OF COMFORT:

- Smooth vibration-free drive
- First ST platform tractor
- Easy gear shifting with fully synchromesh transmission
- Side shift for maximum comfort
- Adjustable suspended seat



EASE OF WORK:

- Independent PTO, reverse PTO & mid PTO
- Finger touch control with double actuating power steering
- Versatile application compatibility for the first time in compact tractors



THE LUXURY OF A CAR:

- Lowest noise tractor
- New-gen instrument cluster
- The comfort of a side shift
- Sleek styling
- Shift gears like your car



1800 419 0136



info@vsttractors.com



www.vsttractors.com



GRAPES



POMEGRANATE



SUGARCANE



SOYABEAN



PADDY



MILLETS



VEGETABLES



MAIZE



COTTON

TECHNICAL SPECIFICATION

AGGREGATES	PARAMETERS	VST 932 DI 2WD/4WD	VST 939 DI 2WD/4WD
ENGINE	Type	Trem IIIA, Naturally Aspirated DI Engine	
	HP (kW) Category	32 (23.5)	39 (28.5)
	No. of Cylinders	3	
	Rated RPM	2500	3000
	Displacement (cc)	1642	
	Cooling	Water Cooled	
	Air Cleaner	Dry Type	
	Max. Torque Nm (Kg-m)	109.4 (11.15)	107.2 (10.93)
TRANSMISSION	PTO HP (kW)	24 (18.65)	28.85 (21.51)
	Gear Box Type	Fully Synchromesh	
	No. of Gears	9 Forward + 3 Reverse	
	Shifting	Side Shift	
	Speed Forward (km/hr)	2.08 - 22.3 / 2.08 - 25.65	2.28 - 28.05
CLUTCH	Speed Reverse (km/hr)	2.21 - 13.86	2.42 - 15.18
	Type	Double Clutch	
PTO	IPTO	540@2340, 1004@2500	
	RPTO	540@1937	
	Mid PTO	Mid PTO	
HYDRAULICS	Type	Auto Draft & Depth Control (ADDC)	
	Three Point Hitch	Category I & II	
	Lifting Capacity (kg)	1250	
BRAKES	Type	Oil Immersed Brakes	
STEERING	Type	Power Steering	
FUEL TANK	Capacity (ltrs)	25	
TYRES	Wheel Drive	2WD / 4WD	
	Front - 2WD	5 x 15	
	Front - 4WD	6 x 12, 7 x 14	
	Rear	9.5 x 20, 11.2 x 24	
DIMENSIONS	Overall Length (mm)	2510	2540
	Overall Width (mm)	Front: 1070, 1190 Rear: 1130 (std), 1470	Front: 1180 Rear: 1245
	Overall Height (mm)	1390	1400
	Wheel Base (mm)	1520	
	Ground Clearance (mm)	325	330
	TCR with Brakes (m)	2.6	
	Total Weight (Kg)	1240 (unballasted)	1260 (unballasted)

Parameters	VST 932	TAFE 30 DI	Swaraj 724 XM	Force OX 25
HP	32	25	24	27
No. of Cylinders	3	2	2	2
Gearbox	H-L-M	L & H	L & H	L & H
No. of Speeds	12	10	8, / 10	10
PTO Power	24	20.3	19.98	23.2



Trust of >5 Lakh Farmers,
Legacy of >50 Years



Widest Product Range
(17 HP to 50 HP)



No.1 Power Tiller Brand
for Last 50 Years



Pioneer in 4WD
Compact Tractors



Global Footprints
in > 40 Countries



Year on Year
Growth Rate > 20%



**VST TILLERS
TRACTORS LTD.**

Regd. Office: Plot No- 1, Dyavasandra Indl. Layout, Whitefield Road,
Mahadevapura Post, Bengaluru-560048, Karnataka. INDIA
Phone: +91 - 80 - 67141111, e-mail: info@vsttractors.com,
CIN: L34101KA1967PLC001706. www.vsttractors.com

Please contact your nearest dealership for latest updates

Authorised Dealer

Disclaimer: Pictures used here are for illustration purpose only. Product specifications are subject to change without prior notice.
Performance of the machine may vary with user/field/working conditions.



1800 419 0136

[f/vsttillers](https://www.facebook.com/vsttillers)

[in/company/vst-tillers](https://www.linkedin.com/company/vst-tillers)

[http://bit.ly/VSTVideos](https://www.youtube.com/watch?v=VSTVideos)

